



**MANUFACTURER**  
TERMA ARTUR DARIUSZ  
I HELENA SZYMANIUK  
SPÓŁKA JAWNA  
UL. POZNAŃSKA 42A  
76-200 SŁUPSK

**UNIQUE IDENTIFICATION CODE OF THE PRODUCT - TYPE**  
EXTERNAL WINDOWS AND DOORS  
WITHOUT RESISTANCE TO FIRE AND/OR SMOKE  
LEAKAGE CHARACTERISTICS  
**IDEAL 7000 SYSTEM**

**NOTIFIED BODY**  
№ 1827  
LABORATORIUM TECHNIKI  
BUDOWLANEJ S.C.  
B. WÓJTOWICZ, A. ZYLJA, M. ZYLJA  
UL. ŁASKI 83 41-306 DĄBROWA  
GÓRNICZA

**CONFORMITY ASSESSMENT SYSTEM**  
**3**



**YEAR OF INTRODUCTION**  
**14**

**DECLARATION OF PERFORMANCE NO. Z/2015/O**

INTENDER FOR THE USE IN PREMISES OF RESIDENTIAL AND PUBLIC BUILDINGS

ON THE BASIS OF THE LABEL WITH THE SERIAL NUMBER

BASE ON THE HARMONISED TECHNICAL SPECIFICATION EN 14351-1+A1:2010

PRODUCT CODE	RESISTANCE TO WIND LOAD - DEFLECTION OF THE FRAME	RESISTANCE TO WIND LOAD - TEST PRESSURE	WATER TIGHTNESS - NON-SHIELDED (A)	OPERATING FORCES	MECHANICAL STRENGTH	LOAD BEARING CAPACITY OF SAFETY DEVICES	AIR PERMEABILITY	DAINGEROUS SUBSTANCES
SINGLE-SASH WINDOWS AND BALCONY DOORS	NPD	NPD	E 1500	NPD	NPD	350 N	Class 4	None
WINDOWS AND BALCONY DOORS WITH MAXIMUM FOUR SIDE HINGED SASHES	C	3	5A	NPD	NPD	350 N	Class 4	None
WINDOWS AND BALCONY DOORS WITH MOVABLE POST	C	2	6A	NPD	NPD	350 N	Class 4	None
MULIONED WINDOWS WITH MAXIMUM DOUBLE TRANSOM	B	2	6A	NPD	NPD	350 N	Class 4	None
SINGLE EXTERNAL DOORS	C	3	7A	NPD	NPD	350 N	Class 4	None
DOUBLE EXTERNAL DOORS	C	2	6A	NPD	NPD	350 N	Class 3	None

THERMAL TRANSMITTANCE U <sub>w</sub> FOR THE REFERENCE WINDOW*		ACOUSTIC PERFORMANCE**						
U THERMAL TRANSMITTANCE OF THE FRAME (W/m <sup>2</sup> K)	W OF THE SPACER (W/m <sup>2</sup> K)			R <sub>w</sub> AIRBORNE SOUND INSULATION OF THE INSULATED GLASS PANEL (dB)	AIRBORNE SOUND INSULATION R <sub>w</sub> (dB) FOR THE TOTAL SURFACE AREA OF THE WINDOW (F)			
	W-0.07	W-0.04	W-0.032		F=2.7m <sup>2</sup>	2.7m <sup>2</sup> -F=3.6m <sup>2</sup>	3.6m <sup>2</sup> -F=4.6m <sup>2</sup>	F=4.6m <sup>2</sup>
1,1	1,2	1,2	1,1	27	30	29	28	27
1,0	1,2	1,1	1,1	28	31	30	29	28
0,9	1,1	1,0	1,0	29	32	31	30	29
0,8	1,0	1,0	0,9	30	33	32	31	30
0,7	1,0	0,9	0,9	32	34	33	32	31
0,6	0,9	0,8	0,8	34	35	34	33	32
0,5	0,83	0,76	0,74	36	36	35	34	33

\* Frame with the size of 1230 x 1460 mm with various glazing and spacers

\*\* Values determined in accordance with section B.6 of the Annex B to EN 14351-1+A1:2010 standard for frames with various types of glazing

NPD - no performance determined

**DYREKTOR**  
*[Signature]*  
mgr inż. Mirosław Fryczek

Słupsk, 01/09/2015